



BurnBoss T-22 & T-24

SERVICING SPECIFICATIONS Parts List for Routine Service of Kubota Industrial Diesel Engine Z482-E3

Also Refer to Engine Manufacturer's Service Manual for Engine Service Details
(Engine should be serviced every 200 hours of operation)

| Description | Air Burners P/N | Manufacturer's P/N |
|---|-----------------|-----------------------|
| Air Cleaner Element | 3060-1022 | Kubota 1G659-11222 |
| Oil Filter | 3060-1020 | Kubota HH150-32430 |
| Fuel Filter | 3060-1021 | Kubota 70000-43081 |
| V-Belt (Engine) | 3060-1023 | Kubota 15881-97010 |
| MAXI Fuse 40A | 5000-0302 | n/a |
| CAT Battery (12V, CCA 800, AH 50) | 5000-2050 | CAT 8C-3612 |
| Optima Battery Red Top (12V, CCA 800, AH 50) | 5000-0199 | OPTIMA SC34A |

| | |
|----------------|---|
| Tire Pressure | 80 psi |
| Tire Size | LT 215 85 R16 |
| Engine Oil | 15W40 Diesel Grade |
| Engine Coolant | Low Silicon Anti-Freeze (Green) Units are shipped from factory with 50-50 mixture green antifreeze/water |
| Hydraulic Oil | ISO32 Synthetic Hydraulic oil, factory installed is Amsoil HVH05-EA. (cold weather option is ISO22 synthetic, i.e. Amsoil HVG05EA) Capacity is approximately 2.16 gallons (8.19 liters). |

Fuel Tank Capacity: Min. 9.9 Gallons (US) or 37.5 Liters