



T-400

SERVICING SPECIFICATIONS Parts List for Routine Service of Kubota Industrial Diesel Engine V3600-TE

Also Refer to Engine Manufacturer's Service Manual for Engine Service Details
(Engine should be serviced first after 50 hours then every 200 hours of operation)

Description	Air Burners P/N	Manufacturer's P/N	NAPA P/N
Air Filter (primary)	5000-1332	Donaldson P828889	6562
Air Filter (safety)	5000-1333	Donaldson P829333	6569
Oil Filter	5000-1326	Kubota HH1C020-32430	7430
Fuel Filter	5000-1299	Kubota 16631-43560	3393
Fuel/Water Separator Filter	5000-1297	Racor R20P	3614
V-Belt (Engine)	5000-1339	Kubota 1G521-97010	259400
V-Belt (Air Fan, 2 Belts)	5000-0008	Optibelt Redpower II 5V1400	-
Electrical System Fuse 40A Amp ID: Green, Style: MAXI	5000-0302	NAPA BK7821079	BK7822102
Optima Battery Red Top (12V, CCA 800, AH 50)	5000-0199	OPTIMA SC34U	-

Tire Pressure	65 psi (4.48 Bar)
Tire Size	22575D15 Trailer Tire (8 Ply)
Engine Oil	15W40 Diesel Grade
Engine Coolant	Low Silicon Anti-Freeze (Green) Units are shipped from factory with 50-50 mixture green antifreeze/water; set at factory to about -32°F
Wheel Lug Nuts Torque	80 ft lbf (108 Nm)
Break-Away Battery (Optional)	Battery 12V Hopkins P/N HM20008 (3-1/2" L x 2-3/4" W x 4" H)
Fuel Tank	Capacity: Min. 45 Gallons (US) or 170 Liters

Rev.11.2015/Q1